


NEW

**BINKS**  
**SuperEfficiency**

**Spraybooth Filter**

Binks have been producing the Best Spray Booth Filters for over 30 years in our own factory in Scotland.

Now, following exhaustive field trials and evaluations we are proud to introduce our NEW SUPER FILTER. Binks Super Filter is constructed from two sheets of heavy duty card board paper and formed into double "accordion" type folds, stapled, glued and backed with a high efficiency polyester media, which dramatically increases the filter efficiency and "loading capacity".



■ Super Filter –  
outlasts other filters

■ Four Face Filter Technique  
PLUS additional "Final Stage"  
polyester filter

■ Superior Construction –  
Glued & Stapled

■ Over 99% filtration efficiency –  
super filter removes very fine  
overspray particles

■ High Loading Capacity –  
Longer Working Life – low pressure drop

■ Fits ALL types of dry filter Spray Booths

■ Expansion strapping – ensures correct  
spacing of filter corrugations

■ Moisture resistant and  
Self Supporting

■ Concertina design –  
reduces storage and  
transportation costs.



**Call Our Hotline Now  
For The Best Prices!**

**Approved Distributor**

**NEW** **BINKS**  
**SuperEfficiency**  
**Spraybooth Filter**

**HIGH VOLUME FLOW RATES**

The large air openings in the filter allow high volumes of air to be exhausted without loss of efficiency as the media 'loads', resulting in a much longer life than other filter systems.



Typical three tier dry filter spraybooth



Bright white spray face - improves spraybooth lighting conditions



Final stage polyester backing provides super efficiency filtration



Superior quality construction with strapping to ensure correct fitting and spacing

**SUPERIOR UNIQUE DESIGN**

Binks super efficiency spraybooth filters are **glued** and **stapled** together during the manufacturing process and an expansion strap on the rear is provided to ensure correct spacing of 8 corrugations to every running foot (30.4cm). This guarantees optimum and superior filtering performance.

Part No	Surface Area	Filter Size Per Box	Weight Per Box
20 72 29 SEF	5.4 SQ MTRS	H90 X L600CM	8.05 KG (INC. BOX)
20 79 02 SEF	8 SQ MTRS	H100 X L800CM	10.26 KG (INC. BOX)

**TECHNICAL SPECIFICATION**

<b>Filter Construction</b>	SELF SUPPORTING, 2 PLY HIGH STRENGTH CARDBOARD PAPER, BRIGHT WHITE FINISH
<b>Air Flow Rates</b>	0.5-1.0 METRES PER SECOND (100-200 FEET PER MINUTE) NORMAL 0.7 M/S (140 FPM)
<b>Pressure Differential</b>	INITIAL @ 0.75 M/S = 30 PA (0.12" SWG) MAXIMUM 130-250 PA (0.52"-1.0" SWG)
<b>Temperature Range</b>	MAXIMUM 100°C
<b>Expansion Limiter</b>	EXPANSION LIMITING STRAPS ENSURE CORRECT PLEAT
<b>(Guarantees optimum performance)</b>	DENSITY OF 8 CORRUGATIONS PER RUNNING FOOT (30.4CM)

**ITW Industrial Finishing**

Ringwood Road, Bournemouth, BH11 9LH England  
 Tel: +44 (0)1202 571111  
 Fax: +44 (0) 1202 573488  
 Email: industrial.mktg@itwfinishing.co.uk

**ITW Oberflächentechnik GmbH & Co. KG**

Justus-von-Liebig-Strasse 31, D-63128 Dietzenbach  
 Tel: +49 (0) 6074-403-1  
 Fax: +49 (0) 6074-403-300  
 Email: marketing@itw-finishing.de

**ITW Surfaces et Finitions**

163-171 Av des Auréats,  
 26014 Valence cedex FRANCE  
 Tel: +33 4 75 75 27 00 Fax: +33 4 75 75 27 59  
 Email: mkt@itwssf.com

**ITW Industrial Finishing**

Binks • DeVilbiss • Gema • Ransburg

**www.itweuropeanfinishing.com**